

### DEPARTMENT OF DEFENSE

# MANAGEMENT AND STANDARDS OF DOD LOCOMOTIVES

**JUNE 1985** 

1

ASSISTANT SECRETARY OF DEFENSE (MANPOWER, INSTALLATIONS & LOGISTICS)

#### OFFICE OF THE ASSISTANT SECRETARY OF DEFENSE



WASHINGTON, D. C, 20301-4000

MANPOWER,
INSTALLATIONS
AND LOGISTICS

June 19, 1985

#### FOREWORD

This Regulation is issued under the authority of the Department of Defense (DoD) Instruction 4140.50, "Management of DoD Locomotives," December 9, 1982. Its purpose is to prescribe uniform procedures to execute the management policy set forth in DoDI 4140.50.

The provisions of this Regulation apply to the Office of the Secretary of Defense (OSD), the Military Departments the Organization of the Joint Chiefs of Staff, and the Defense Agencies (hereafter called "DoD Components").

This Regulation is effective immediately and will be used by all DoD Components. Heads of DoD Components may issue supplementary instructions to provide more detailed guidance if required. Existing publications of the Department of the Army relating to the various phases of locomotive management may be used by other DoD Components in lieu of publishing their own instructions.

Send recommended changes to this Regulation to the Chairman, Interservice Locomotive Management Committee (Deputy Chief of Staff for Logistics, Headquarters, Department of the Army Attention: DALO-TSM).

DoD Components may obtain copies of this Regulation through their respective publications channels. Other federal agencies and the **public may** obtain copies from the Director, US Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Robert W. Daniel, Jr.

Deputy Assistant Secretary of Defense (Logistics and Materiel Management)

Sobert W. Danul, 1-

#### MANAGEMENT AND STANDARDS OF DOD LOCOMOTIVES

1

#### TABLE OF CONTENTS

CHAPTER 1	GENERAL INFORMATION	Page
	A. Purpose B. Applicability c. Responsibilities D. Procedures E. Definitions F. Reporting Requirements	1-1 1-1 1-1 1-2 1-2 1-3
CHAPTER 2	INTERSERVICE LOCOMOTIVE MANAGEMENT COMMIT	CEE
	A. Objective	2-1
	B. Review of Locomotive Management Information	2-1
	c. Locomotive Replacement and Distribut. Plans	ion 2-1
	D. Membership of the Interservice Locomo Management Committee (ILMC)	otive 2-1
	E. TLMC Meetings	2-2

CHAPTER 3 ,	LOCOMOTIVE MANAGEMENT INFORMATION SYSTEM	Page
	A. Usage Standards B. Inventory c. Rail Data File Layout D. Description Definitions E. Reporting Requirements	3-1 3-1 3-1 3-2 3-2
CHAPTER 4	MANAGEMENT OF LOCOMOTIVES	
	A. Genera 1 B. Commercial Carrier Switching Service	4-1 4-1
CHAPTER 5	AUTHORIZATION OF LOCOMOTIVES	
	A. Policy B. Requirements c. Authorization	5-1 5-1 5-1
CHAPTER 6	SELECTION OF LOCOMOTIVES	
	A. Analysis of Requirements	6-1
	B. Formulas and Factors for Locomotive Selection	6-1
	c. Characteristics of and Planning Factors For DoD Locomotives	6-5



CHAPTER	7	ACQUISITION OF LOCOMOTIVES	Page
	·	A. Standardization B. Procurement Criteria c. Procurement Planning	7-1 7-1 7-1
CHAPTER	8	MAINTENANCE SUPPORT FOR LOCOMOTIVE EQUIPMENT	
		A. Responsibilities B. Repair part supply support c. Repair part stock D. Mandatory inspections E. Funding F. Sources of Maintenance support for locomotive equipment	8-1 8-1 8-2 8-2 8-2
CHAPTER	9	REPAIR AND REPLACEMENT STANDARDS FOR LOCOMOTIVES	
		A. General B. One-Time Repair Expenditure Limits c. Technical Inspections D. Computation of Repair Cost Estimates E. Disposition	9-1 <b>9-1</b> 9-2 9-2 9-6

CHAPTER 10		STORAGE OF LOCOMOTIVES	Page
ŕ	A. B. c. D.	Policy Storage Locations Storage at User Installations Long Term Storage	10-1 10-1 10-2
CHAPTER 11	SAFI	ETY	
	<b>A.</b> B.	Operating and Safety Rules Safety Requirements - Locomotives	11-1 11-1
APPENDIX			
	Α.	Maintenance Repair Expenditure Limitation for FSCC 2210 (Locomotives)	A-1
	В.	References	B-1

#### GENERAL INFORMATION

#### A. PURPOSE

- 1. This regulation establishes procedures to execute DoD Instruction 4140.50. It designates a point of contact for DoD locomotive management information, a representative to chair the Interservice Locomotive Management Committee (ILMC), and the membership of the committee. It also establishes locomotive usage standards, locomotive replacement criteria, and procedures for maintaining current information on location, age, condition and usage of all locomotives in the Department of Defense.
- 2. It establishes the duties of the **Interservice** Locomotive Management Committee and provides guidance on locomotive management, including authorization, selection of equipment, maintenance support, acquisition, and safety.
- 3. The regulation is designed to facilitate interservice support and coordination among the DoD Components in the management of DoD locomotives, and to establish a centralized inventory reporting system to readily identify locomotives available for assignment or reassignment to other services. .

#### B., APPLICABILITY

The development and maintenance of this regulation is authorized by DOD Instruction 4140.50, "Management of DoD Locomotives." The regulation applies to the Military Departments and the Defense Agencies (hereafter referred to as "DoD Components").

#### c. RESPONSIBILITIES

- 1. The <u>Secretary of the Army</u> shall:
- a. Serve as the executive agent for the procurement of locomotives in the Department of Defense.
- b. Designate a point of contact for DoD locomotive management information.
- c. Pursuant to his responsibilities, establish and chair an Interservice Locomotive Management Committee, The Deputy Chief of Staff for Logistics, Headquarters, Department of the Army, will provide a GM13 representative to chair the Interservice Locomotive Management Committee.
  - 2. The DoD point of contact for locomotive management information shall:
    - a. Mantain current DoD locomotive replacement criteria.

- b. Execute and maintain the Locomotive Management Information System specified in Chapter 3.
- c. Provide DoD Components, as requested, with current information on location, age, condition, and usage of locomotives in the Department of Defense.
- d. Provide a representative to serve as an ex officio member of the **Interservice** Locomotive Management Committee.

#### 3. DoD Components shall:

- a. Provide input for the Locomotive Management Information System to the DoD point of contact in accordance with Chapter 3.
- b. Advise DoD point of contact of its designated manager for locomotive management information and HQDA of its representative to the Interservice Locomotive Management Committee (ILMC).

#### D. PROCEDURES

This regulation is tailored to provide policy guidance solely for locomotive management, although it is recognized that the operation of DoD rolling stock is often an intrinsic part of the locomotive management function. This regulation may be augmented by the DoD Components to prescribe more detailed instructions, if necessary. Existing publications of the Army on the various phases of locomotive management may be used by the other DoD components instead publishing their own regulations. Joint service regulations are encouraged as an interim measure to ensure complete compliance with this regulation. Matters requiring issuance of DoD policy, or amendment, or clarification of this regulation should be referred to the chair of the ILMC. An objective of the ILMC is to consolidate, when possible, the DoD component publications into this regulation to minimize the growing number of regulations, and ensure uniformity of policy and instructions.

#### E. <u>Definitions</u>

- 1. <u>Motive Power</u>. Railroad locomotives and other self-propelled equipment designed for moving rolling stock. This includes self-propelled rail cars designed to carry freight and/or passengers within the body of the car and car movers designed to operate interchangeably on either rubber tires or **steel** flanged wheels.
- 2. <u>Rolling Stock</u>. Railroad cars used for the movement of freight or passengers which must be moved by a locomotive or other external means. Railroad cars are further categorized by their use or design as box, flat, depressed center flat, gondola, hopper, dump, tank, caboose and passenger.
- 3. <u>Utility Railroad</u>. Railroads that connect with rail carrier lines and range from a simple siding to a warehouse or series of warehouses to a complete rail network with interchange tracks, switching leads, repair tracks, inspection

tracks, and any additional tracks necessary to facilitate the receipt and delivery of carload freight and provide a network for intra-installation transportation.

#### F. REPORTING REQUIREMENTS

The  $\acute{\text{Utilization}}$  Report specified in Chapter 3, paragraph E. is assigned Report Control Symbol DD-MIL(A)1683 in accordance with reference 3, TAB B.

March Const.

#### CHAPTER 2

#### INTERSERVICE LOCOMOTIVE MANAGEMENT COMMITTEE (ILMC)

#### A. OBJECTIVE

The primary objective of the **Interservice** Locomotive Management Committee (**ILMC**) is to conduct periodic reviews of locomotive management information and coordinate DoD Component locomotive replacement and distribution plans. A secondary objective of the **ILMC** is to facilitate an integrated management system for DoD locomotives through analysis of the locomotive  $\square$  anagement information and an interchange of expert advice. Regulations and policies of the DoD Components shall be reviewed and consolidated to the maximum extent and when feasible incorporated into this regulation by amendment.

#### B. REVIEW OF LOCOMOTIVE MANAGEMENT INFORMATION

A comprehensive review by each member of the ILMC shall be made of the locomotive management information furnished by their DoD component.' An analysis of the information shall be presented by each committee member at the annual meeting of the committee. The committee shall advise and assist the individual DoD Components in improving management techniques to achieve maximum usage of its assigned motive power; discussions shall be held on common management problems, and solutions will be sought that can be uniformly applicable within the DoD. Information reporting procedures shall be reviewed annually to determine if revisions should be made to the LMIS system.

#### c. LOCOMOTIVE REPLACEMENT AND DISTRIBUTION PLANS

The committee shall review the replacement and distribution plans of the locomotive managers of the DoD Components to determine if redistribution of excess or under utilized locomotives is feasible. Loans of locomotive equipment to satisfy short-term or temporary requirements shall be considered. The use of Interservice Support Agreements shall be encouraged by the ILMC to reduce the locomotive resource requirements within the DoD.

#### D. MEMBERSHIP OF THE INTERSERVICE LOCOMOTIVE MANAGEMENT COMMITTEE (ILMC)

Permanent members of the committee have been designated by the heads of the DoD Components as indicated:

- 1. Chair of **ILMC.** Designee of the Deputy Chief of Staff for Logistics-, Headquarters, Department of the Army.
- 2. Member. Designee of the Commander, Naval Facilities Engineering Command.
- 3. Member. Designee of the Commander, Headquarters, Air Force Logistics Command.
  - 4. Member. Designee of the Commandant, Headquarters, U.S. Marine Corps.

5. Member. Designee of the Director, Headquarters, Defense **Logistics** Agency.

6. Ex Officio Member. To be designated by the DCSLOG, HQDA.

The Chair may request the participation of technical or management experts in the meetings of the committee as required to accomplish the objectives of the ILMC.

#### E. <u>ILMC Meetings</u>

The committee shall meet annually at time and place designated by the Chair. Additional meetings may be scheduled by the Chair as necessary to achieve the objectives of this regulation.



#### LOCOMOTIVE MANAGEMENT INFORMATION SYSTEM

#### A. USAGE STANDARDS

The Heads of the DoD Components shall ensure that all installations within their respective Services that operate locomotives have a reporting system that can be effectively used to measure the utilization of the equipment. Due regard will be given to the mission of the installation, and the system may be tailored to reflect the peculiarities or constraints of certain installations. Existing systems for reporting utilization may be used if they contain—the common measurable factors specified in the Section C, Locomotive Data File Layout, Columns 34 through 55. The utilization reporting system is to be based on transportation performance factors for rail operations. The common measurable standards are total switch movements, total rail cars switched, intraplant car movements, inbound and outbound cars interchanged with the commercial carriers serving the installation, and similar operating data maintained in accordance with the DoD Components management and performance standards.

#### B. INVENTORY

The Heads of the DoD Components shall designate a manager within their respective services to maintain a master inventory record by locomotive type and location.

#### c. RAIL DATA FILE LAYOUT

<u>COLUMNS</u>	DESCRIPTION
1-13	NSN
14-15	MFG $YR$
16-17	STATE
18-20	WEIGHT
21	MAJOR COMMAND
22	SERVICE
23	BLANK
24-29	LOC CODE (UIC)
30-33	INSP DATE
34-38	OPER HRS
39-42	ANNUAL HRs
43-46	CARS IN
47-50	CARS OUT
51-55	INTRA SWITCHES
56	BLANK
57-71	ROAD NUMBER
72	CONDITION
73	REQUIREMENTS CODE
74-77	ACQUISITION COST

#### Data will be in:

- 1. 80 Column Card Form
- 2. Magnetic Tape, Autodin Record Length 80 Characters, **BLKSIZE** 3200 **(40** Records/block)

#### D. DESCRIPTION DEFINITIONS

NSN-National Stock Number where known or established identification number.

MFG YR -- Calendar year locomotive manufactured or remanufactured in.

STATE -- State that installation and locomotive are located in.

WEIGHT -- Tonnage of locomotive.

MAJOR COMMAND -- Major Command to which installation is assigned.

D--DARCOM, F--FORSCOM, T--TRADOC, M--MTMC

SERVICE-DOD Component -- A-Army, N-Navy, F-Air Force, M-Marine Corps, S-Defense Logistics Agency

LOC CODE (UIC) -- Alpha-Numeric for each location.

OPER HOURS -- Total accumulated hours since overhaul or remanufacture

SEMI-ANNUAL HOURS -- Total hours locomotive operated last 12 months

CARS IN -- Number of rail cars received (loaded or empty) by installation during past 12 months

INTRA SWITCHES -- Each rail car moved and spotted at a differnt location within an installation

ROAD NUMBER -- Reporting marks and numbers identifying each locomotive CONDITION CODE -- A-Serviceable, F-Unserviceable, M-Being remanufactured or overhauled -- or MIL-STRIP Condition Code

REQUIREMENTS CODE -- 1-In Use-Serviceable, 2-Stand by-Serviceable, 3-Contingency-Serviceable, 4-Storage-Serviceable 5-Storage-Unserviceable, 6-Excess-Serviceable, 7-Excess-Unserviceable, 8-Loan, 9-In Transit

ACQUISITION COST -- Cost in \$000's

#### E. REPORTING PROCEDURE

- 1. The usage report and locomotive inventory data required by Sections A and B shall be submitted by the designated DoD Component managers on a **annual** basis to TROSCOM, the DoD point of contact for locomotive management information. The information will be transmitted in the rail data file layout specified in Section C not later than 20 January each year.
- 2. TROSCOM will produce a hardcopy data base print, on request, and will provide each LMIC member a copy. Format for usage report hardcopy report is to be developed by TROSCOM.



#### MANAGEMENT OF LOCOMOTIVES

#### A. GENERAL

1

Locomotives are characterized by a high initial acquisition cost, an extended procurement lead time, minimal technical obsolescence, and a long effective lifespan. These factors dictate a comprehensive analysis of locomotive requirements and a thorough review of all feasible alternatives to the ownership of this equipment. It is DoD policy to maintain and operate in peacetime a diversified fleet of motive power to provide for logistic needs and essential training of operational personnel to assure military effectiveness in support of national defense policies. Locomotives shall be cquired and utilized with due regard to the availability of commercial transportation. Within the intent of this regulation, the considerations to be given to the use of commercial transportation are outlined in Sections B below.

#### B. COMMERCIAL CARRIER SWITCHING SERVICE

Rail Carrier Obligations: Line haul rates offered by carriers shall be deemed to include delivery to the unloading spot. Further, rail carriers may deliver on and remove cars from privately owned side tracks and industrial tracks connecting with a carrier's tracks, cars of freight moving at carload rates, without additional charge, provided there are no conditions that make it unsafe for the carrier's locomotives to operate over such tracks or that prevent carriers from receiving or delivering the cars at its ordinary operating convenience in a continuous movement.

- 1. "Continuous movement" means a movement between the carrier's tracks and the loading or unloading locations, a hold track or tracks, or other place where cars are received or delivered without any delay, or any suspension, or break in time, or continuity of the movement, due to any circumstances or condition for which the industry is directly responsible.
- 2. "Ordinary operating convenience" means the time selected by the carrier when it is most advantageous to the carrier, in relation to its coordinated switching activities in a particular switching zone, when the terminal services are performed by switching locomotives, or at the time the scheduled trains arrive at the plant site when the switching services are performed by road switcher. Ordinarily, it contemplates only one switch a day, except when additional switches are made for carrier convenience to secure the prompt release of equipment or when necessitated by the volume of traffic. Movements to, from, or within the plant site at other times, at the request of the industry are not considered at the carrier's ordinary operating convenience.
- 3. Switching services required beyond the carrier's obligation for initial placement of a car, such as **intraplant** switching and weighing operations performed by the installation for its own convenience are transportation services that the carrier is normally not obliged to perform. However, these special switching services can be performed by carrier when agreed to special charges are published. The installation Transportation Officer should request the rail carriers to establish **special** charges for these services if such agreements are not on file. The switching services of the rail carriers shall be used to the



maximum extent possible. Shipping, receiving and warehousing activities shall be scheduled and coordinated to gain full benefit of the carrier's services, augmented by the carrier's special contracts for repotting, intraplant switches, weighing and similar services.

4. Assistance may be requested through channels from the Commander, MTMC, if a satisfactory agreement cannot be reached with the concerned rail carriers.

#### AUTHORIZATION OF LOCOMOTIVES

#### A. POLICY

1

*3-22-22-22-23* 

Prior to requesting the assignment of a DoD locomotive, the DoD component initiating the request shall make an administrative determination that the installation requesting the locomotive has:

- 1. Not been able to secure switching service on a tariff basis from the serving rail carrier or carriers.
- 2. Complied with the provisions of OMB Circular No. A-76 and the implementing DoD Instruction 4100.33, "Operation of Commercial and Industrial-Type Activities," and the associated DoD 4100.33-H, "DoD In-House Vs Contract Commercial and Industrial Activities Cost Comparison Handbook."
- 3. Determined it is not economically feasible to transfer the rail traffic to an alternate transportation mode.
  - 4. It is necessary to meet mobilization requirement.

#### B. REQUIREMENTS

Locomotive requirements shall be compatible with the organizational structure and mission of the installation.

- 1. Locomotives shall be required on a continuing basis.
- 2. There **is** no suitable substitute type locomotive available at the installation.

#### c. AUTHORIZATION.

An authorization document shall be issued by the Head of the DoD Component or his designee specifying the type and quantity of locomotives to be assigned to the requesting installation.



#### SELECTION OF LOCOMOTIVES

#### A. ANALYSIS OF REQUIREMENTS

The selection of a locomotive is based on the average daily switching requirements of the installation during both peacetime and mobilization. The majority of the DoD rail operations are utility railroad and intraplant in nature, characterized by relatively short distance switch movements usually consisting of less than ten rail cars per move. Distances from the interchange points with the commercial rail carriers to the installation classification or receiving yards rarely exceed five miles. Therefore, the criteria used by commercial rail carriers for the assignment of motive power are not generally applicable to the operation of a DoD installation. The daily average Gross Trailing Load (GTL) switching requirement of an installation should be used in computing the Drawbar pull (DBP) need for an assigned locomotive. During peak periods an extra switch move may be required to handle an above average volume of cars. This situation is preferable to the acquisition, assignment, use and maintenance of a locomotive larger than that required for the installation's mission. The objective is to assign locomotives of the minimum size and horsepower available that can effectively perform the switching requirements of the installation. Sections B and C contain formula and factors to be used in the selection of a locomotive as well as characteristics of locomotives owned and operated by the DoD Components.

#### B. FORMULAS AND FACTORS FOR LOCOMOTIVE SELECTION

Locomotives will be selected based upon consideration of the following factors.

- 1. Weight on Drivers. Weight on drivers is expressed in short tons; it is that weight supported by the driving wheels of a locomotive. It does not include any of the remaining portion of the locomotive weight. The weight on drivers of some locomotives used by the DoD is shown in Table 1; for those not listed in this table, specifications issued by the purchaser, the using railroad, or the manufacturer  $\square$  ust be consulted.
- 2. Tractive Effort. The force developed at all the locomotive driving wheels parallel to the rail to pove the locomotive and cars. This force is expressed in pounds; it is directly proportional to the locomotive horsepower and inversely proportional to the locomotive speed. The tractive effort of some locomotives used by the DoD is contained in Table 1. Where such data are not available, tractive effort may be determined as indicated in a and b below.
  - a. Starting Tractive Effort (TE).
- (1) Starting tractive effort is the power that a locomotive can , exert to move itself and the load that it is hauling from a dead stop. It is correlated closely to the adhesion which the driver wheels maintain at the rails. If the tractive effort expended exceeds this adhesion factor,

the driving wheels will slip. Normally, the adhesion factor, when the rails are dry, is 30 percent of the weight on drivers; when the rails are wet, this factor is reduced to 20 percent. For planning purposes, 25 percent is used.

WALLEY .

(2) For a diesel locomotive weighing 80 short tons (73 metric tons) or 160,000 pounds (72,574 kilograms) on the driving wheels, the starting tractive effort is computed as follows:

TE = Weight on drivers (lb(kg))

25% adhesion factor

= 
$$\frac{160,000 \text{ lbs } (72,574 \text{ kgs})}{4}$$
= 40,000 lbs (18,143 kgs)

b. Continuous Tractive Effort TE . Continuous tractive effort is the effort required for the locomotive to keep a train rolling after it has been started. As the momentum of a train increases, the tractive effort necessary to keep the train moving diminishes rapidly. Since a diesel-electric locomotive cannot continue to exert the same force while pulling a load as was attained in starting that load, the continuous tractive effort of a diesel-electric locomotive is rated as approximately 50 percent of its starting tractive effort. For a diesel-electric locomotive weighing 80 short tons (73 metric tons) or 160,000 pounds (72,574 kilograms) on the driving wheels, the continuous tractive effort is computed as follows:

$$TE_c = TE$$
2

=  $\frac{40,000 \text{ lbs } (18,143 \text{ kgs})}{2}$ 
= 20,000 lbs (9,071 kgs)
3. Drawbar Pull (DBP)

a. Drawbar pull is the force available to pull a train after deducting from tractive effort the energy required to move the locomotive itself. In planning, 20 pounds per ton of total locomotive weight is taken from the tractive effort as follows:

Total locomotive wt = 100 STON  $100 \times 20 = 2,000 \text{ pounds}$ TE minus 2,000 pounds = DBP

or

$$TE = \frac{200,000}{4} = 50,000$$

$$TE = \frac{50,000}{2} = 25,000$$

b. Maximum drawbar pull can be exerted only at lowest speeds up to about 10 miles (16 kilometers) an hour and for a limited length of time; at higher speeds, diesel-electric locomotive drawbar pull diminishes rapidly because the electric generator and traction motor cannot hold up under the heavy starting voltage and amperage, and would burn out if the load continued for a longer time after the locomotive reached a speed of 10 miles per hour. However, a steam locomotive retains its initial drawbar pull at all speeds

in the same manner that it retains its tractive effort at all speeds.

- 4. Rolling Resistance (RR) The force components acting on a train in a direction parallel with the track, which tend to hold or retard the train's movement, constitute rolling resistance. The components of rolling resistance are friction between the railheads and the treads and flanges on the wheels, resistance due to undulation of track under a moving train, internal friction of rolling stock, and resistance in still air. There is no absolute figure to be used for rolling resistance, but experience indicates that safe average values to use for rolling resistance are as shown in table 2.
- 5. <u>Grade Resistance (GR)</u> Grade resistance is the resistance offered by a grade to the progress of a train. It is caused by the action of gravity, which tends to pull the train downhill. For military railway planning, use the factor of 20 pounds multiplied by the percentage of grade resistance in pounds per ton of trailing load (train).
- 6. Curve Resistance (CR) Curve resistance is the resistance offered by a curve to the progress of a train. No entirely satisfactory theoretical discussion of curve resistance has been published; however, engineers in the United States usually allow from 0.8 to 1 pound per ton of train per degree of curve. In military railway planning, use the factor of 0.8 pound multiplied by the degree of curvature.

#### 7. Weather Factor (W)

.....-

- a. The weather factor reflects, by percentage, the adverse effect of cold and wet weather on the hauling power of a locomotive. Experience and test have proved that, whenever the outside temperature drops below 32 Degree Fahrenheit, the hauling power of a locomotive is decreased. Table 3 indicates the weather factor (percent) for varying degrees of temperature.
- b. Ordinarily, wet weather is regarded as **local** and temporary; it **is** considered absorbed by average figures. However, in countries having extended wet seasons (monsoons, fog, etc.), the 10ss of tractive effort due to **slippery** rails may prove serious if sanding facilities are lacking or inadequate. The applicable reduction is a matter of judgement, but in general, tractive effort will not be reduced to less than 20 percent of the weight on drivers.

#### 8. Gross Trailing Load (GTL)

a. When diesel-electric locomotives are operated in multiple unit operation, the gross trailing load is equal to sum of the gross trailing load for all locomotives so used. However, when the locomotives are not

electrically **connected** for multiple unit operation, or when steam locomotives are used **in** tandem (doubleheaded) or in pusher service, 10 percent of the total gross trailing load is deducted because of the human element involved.

b. Gross trailing load is the maximum tonnage a locomotive can move under given conditions; for example, curvature, grade, and weather. It is determined by combining the factors discussed in paragraphs 12-6 through 12-10. The formula for gross trailing load follows:

$$GTL = \frac{DBP \times W}{RR + GR + CR}$$

where --

GTL = gross trailing load

DBP = drawbar pull

w = weather resistance
RR = rolling resistance
GR = grade resistance
CR = curve resistance

c. When multiple unit diesel **locomotives** or pushers are used, the gross trailing load is equal to the sum of the gross trailing load for all locomotives used.

#### c. CHARACTERISTICS OF AND PLANNING FACTORS FOR SOME DoD LOCOMOTIVES

Table 1. Characteristics of Some DoD Locomotives

						Tractive f	Tractive force (pounds)						
Type of locomotive	Gage (inches)	Weight (pounds)	Length over couplers	Extreme width		Starting at 30% adhesion	Contin- Uous	Horse- power	Curvature minimum radius (feet)	Fuel capacity (gallons)			
131-Ton, 0-6-6-0, do- mestic and foreign service, NSN-2210- 554-0786	56½	262,900	55 `	10'0"	14'0"	75,700	<b>28,000</b> at 10 mph	1,000	231	1,600			
127-Ton, 0-6-6-0, do- mestic and foreign service, NSN 2210- 270-1354	56½	261,000	55 '	10'0"	10'0"	75,700	28,000 at 10 mph	1,000	231	1,600			
120-Ton, O-6-6-0, <b>do-</b> mestic and foreign service, NSN 2210- 814-5291 NSN <b>2210-</b> 815-3521-w/generator	<b>56½,60,</b> 63, 66	<b>240,000 246,000</b> w/steam generator	57'5"	9'8"	13'6"	73,000	<b>47,000</b> at 10 mph	1,600	193	1,600 800 w/steam generator			
120-Ton, 0-6-6-0, do- mestic and foreign service, NSN 2210- 819-9317	<b>56½,</b> 60, 63, 66	240,000 246,000 w/steam 'generator	56'9"	9'7"	13'5"	72,000	<b>45,000</b> at 10 mph	1,600	193	1,600 800 w/steam generate			
120-Ton, 0-4-4-0, do- mestic service, NSN 2210-554-0785	56½	240,000	55 ' 9 ''	10'3"	14'6"	75,000	<b>40,000</b> at 11 mph	1,500	150	800			
120-Ton, 0-4-4-0, do- mestic service, NSN 2210-262-0751	56½	246,000	48′10″	10'2"	14'6"	73,000	<b>35,000</b> at 10 mph	1,200	100	750			

Table 1. Characteristics of Some DoD Locomotives Continued

				Tractive force (pounds)													
	Type of locomotive	Gage (inches)	Weight (pounds)	Length over couplers	Extreme width	Extreme height	Starting at <b>30%</b> adhesion	Contin- Uous	Horse- power	Curvature minimum radius (feet)	Fuel capacity (gallons)						
	115-Ton, 0-4-4-0, do- □estic service, NSN 2210-112-8508	56½	230,000	45 ' 6''	10'0"	14'6"	69,000	20,000 at 15 mph	1,000	50	635						
	100-Ton, 0-4-4-0, do- mestic service, NSN 2210-819-9320	56½	199,000	44'6"	10'0"	14'4"	59,700	18,750 at 10 mph	660	50	635_						
66	100-Ton, O-4-4-O, do- □estic service, NSN 2210-371-7535	56½	200,000	44'5"	10'0"	14'7"	69,700	18,750 at 10 mph	800	100	600						
	80-Ton, O-4-4-0, do- mestic service, NSN 2210-820-5451	56½	161,000	36′10″	9'6"	13'7"	48,000	10,000 at 10 mph	500	75	400						
	80-Ton, 0-4-4-0, do- mestic service, NSN 2210-804-3614	56½	161,000	36′10″	9'6"	13' 7"	48,000	10,000 at 10 mph	470	75	400						
	80-Ton, 0-4-4-0, do- mestic service, NSN 2210-804-3615	56½	161,000	41'0"	9'6"	13'4"	48,000	21,000 at 5.2 mph	550	75	400						
	65-Ton, 0-4-4-0, do- mestic service, FSN 2210-819-9319	56½	130,000	34'0"	10'1"	13'5"	39,000	9,500 at 10 mph	400	75	250						

#### c. CHARACTERISTICS OF AND PLANNING FACTORS FOR SOME DOD LOCOMOTIVES

Table 1. Characteristics of Some DoD Locomotives--Continued

			Tonath		<u>11a</u>	<u>ctive forc</u>	<u>ce (pounds</u>	1	Curvature	Fuel
Type of locomotive	Gage (inches)	Weight (pounds)	Length over couplers	Extreme width	Extreme height	Starting at 30% adhesion	Contin- uous	Horse- power	minimum radius (feet)	capacity (gallons)
65-Ton, 0-4-4-0, do- mestic service, NSN 2210-819-9319	56½	130,000	34'0"	10'0"	13'5"	39,000	9,500 at 10 mph	400	250	
60-Ton, 0-4-4-0, do- mestic and foreign service, NSN <b>2210</b> 819-9318	56½, 60	122,000	38'11" (Type E) 39'3" (Willison	9'6"	13'4"	36,000	15,680 at 7.78 mph	500	75	500
45-Ton, 0-4-4-0, <b>do-</b> mestic and foreign service, NSN 2210 529-9038	56½	90,000	33'6"	9'7"	12'0"	27,000	12,000 at 6 mph	380	50	250
45-Ton, 0-4-4 <sup>-</sup> 0, do- mestic service (side rod drive) NSN 2210-821-1135	56½	90,000	28'4"	9 ' 6''	12'0"	27,000	13,500 at 6.2 mph	300	50	165
44-Ton, 0-4-4-0, <b>do- mestic</b> service, NSN 2210-804-3610	56½	91,270	33'10"	9'4"	13'3"	26,400	11,000 at 9 mph	380	75	250
44-Ton, 0-4-4-0, <b>do-</b> mestic service NSN 2210-820-5602	56½	89,000	3315"	10'0"	13'3"	26,400	13,000 at 7.1 mph	380	50	250
25-Ton, O-4-O, do: mestic service NSN 2210-834-3202	56½	50,000	16' 1"	8'7"	10'4"	15,000	6,200 at 6.2 mph	150	50	75

Table 2. Average Value of Rolling Resistance

Pounds	per	ton	of	train	Condition of track
	5 6 <b>7</b> <b>8</b> 9	and	10		Exceptionally good Good to fair Fair to poor Poor Very Poor

Table 3. Effect of Weather on Hauling Power of Locomotives

Most adverse temperature in 'F	Loss in hauling (percent)	Weather factor (percent)
Above +32	0	100
+16 to +32	5	95
0 to +15	10 15	90 85
-11 to <b>-20</b>	20	80
-21 to -25	25	75
-26 to -30	30	70
-31 to -35	35	65
-36 to -40	40	60
-41 to -45	45	55
-46 to -50	50	50

Table 4. Requirement for Locomotives

		Estimated average rate of fuel oil consumption							
Type of locomotive	Type of operation	Gal per train mile	Gal per hour						
Diesel-electric locomotive standard gage:  0-6-6-0, DE, 120-ton  0-4-4-0, DE, 120-ton	Road switcher Road switcher	2.5	11.5 8.0						

Mary States

#### CHAPTER 7

#### ACQUISITION OF LOCOMOTIVES

#### A. STANDARDIZATION

DoD locomotive equipment provided for use in CONUS shall generally be standard, commercially designed equipment conforming to the requirements of the Association of American Railroads (AAR) and the Federal Railroad Administration (FRA). This will ensure the mobility and interchangeability of the equipment as required. Motive power shall be of standard commercial design with types and models acquired being restricted to the minimum number consistent with current and projected requirements. Major components shall be similarly standardized to the maximum extent possible. Procurement of locomotives for foreign service shall be in accordance with the principle of acquiring commercially designed equipment, when practical, with consideration to the configuration limitations caused by clearances, axle loads, curvatures, and other restricting factors.

#### B. PROCUREMENT CRITERIA

To avoid unnecessary military ownership, DoD-owned locomotives, to be eligible for procurement, retention, maintenance, or upgrading must meet one  ${f of}$  the following criteria:

- 1. The locomotive is a type peculiar to the military -- a specialized type not available from commercial sources, or not available in the number or at the time required to meet military needs.
- 2. The locomotive is required to meet overseas or mobilization requirements.
- 3. The equipment is required to meet intra-installation requirements of a military activity.
- 4. The cost of obtaining locomotive service from commercial sources is in excess of the cost of operating military-owned equipment, and it can be determined administratively that it would be wasteful of public funds. This determination must comply with the provisions of **DoD** Instruction 4100.33, **Operation** of Commercial and Industrial-Type Activities.

#### c. PROCUREMENT PLANNING

DoD Components having requirements for locomotive equipment not available in the DoD rail inventory or having future requirements for specialized equipment not available in the DoD or commercial railroad inventory must expeditiously requisition the equipment through appropriate channels. A minimum lead time of twenty four months is required for procurement of specialized equipment and motive power. Prior to submitting a Military Interdepartmental Purchase Request (MIPR) the Interservice Locomotive Management Committee will be requested to determine if suitable locomotives are available within the DoD inventory that would satisfy the requirement of the DoD component with the procurement requirement. Each DoD Component must plan, program, and budget for costs

associated with the acquisition of its locomotives and locomotive equipment. **TROSCOM** is responsible under the DoD Coordinated Procurement Program for the acquisition of locomotives and locomotive equipment.

2.7.3.7

#### MAINTENANCE SUPPORT FOR LOCOMOTIVE EQUIPMENT

#### A. RESPONSIBILITIES

- 1. TROSCOM (Focal Point) is responsible for:
- a. Maintennance of utility rail equipment used by DA and other DoD agencies having Interservice Support Agreements (ISSAs) (DD Form 1144) with TROSCOM.
- b. Operation of Mobile Rail Repair Shops (MRRS) to provide direct and general support maintenance on this equipment. TROSCOM will ensure adequate support is available to handle other service requirements. (See Section F for MRRS locations and areas they service.)

#### 2. Maintenance

- a. Unit Maintenance.
- (1) The using activities are responsible for data reporting, operation, and organizational maintenance of the rail equipment.
- (2) The using activities maintenance personnel, the operator, and crew of the equipment shall perform unit maintenance.
- (3) On request, MRRS can perform unit maintenance for using organizations that lack the personnel, tools, or test equipment needed.
- b. Direct and general support maintenance. Installation commanders are responsible for direct and general support maintenance of assigned or supported equipment.
- c. Depot maintenance. TROSCOM is responsible for depot maintenance of Army locomotives; it shall facilitate and coordinate depot maintenance requirements of other DoD components under the provisions of para a(1), subject to the availability of shop time at depot maintenance facilities.

#### B. REPAIR PARTS SUPPLY SUPPORT

- 1. Using activities will submit requisitions to the proper MRRS for organizational maintenance repair parts not available through normal local supply charnels.
  - 2. MRRS will:
- a. Verify that repair parts requisitioned are required for orgnizational maintenance.
  - b. Supply items by:
    - (1) Shipping from MRRS stock.

1

(2) Making funded requisitions for parts to the proper servicing installation **stock** fund. (Shipment maybe direct to user).

- (3) **Using** the procurement activity of the servicing installation to obtain repair parts not available through source (1) and (2) above. (Shipment will be direct from vendors to installation.)
- (4) Using Standard Form 44 (Purchase Order-Invoice-Voucher) to purchase repair parts locally in emergencies. These local purchases are subject to the limitations set out in Section 13.505-3 of the Federal Acquisition Regulation (FAR).

#### c. REPAIR PART STOCKS

- 1. The MRRS are issued mission stocks and regulated items as authorized.
- 2. The MRRS will replenish stocks by:
- a. Making funded requisitions, except items authorized for local purchase.
- b. Using the procurement activity of MRRS servicing installations for authorized items.

#### D. MANDATORY INSPECTIONS

TROSCOM representatives shall conduct a mandatory annual inspection of all assigned Army locomotives. Inspections will be made for other DoD components who request and provide funds for this service. This inspection shall be conducted regardless of the means of maintenance support and/or the organization providing the support to insure that rail equipment is maintained and reported in compliance with applicable service manuals. Locomotives which are also used on commercial track, will be maintained, inspected, and reported in compliance with the Federal Railorad Administration Regulations and the interchange rules and safety requirements of the Association of American Railroads (AAR).

#### E. FUNDING

- 1. TROSCOM provides funds for direct and general support maintenance and supply support for Class I Army installations directly to MRRS. These installations shall not cite consumer funds on requisitions.
- 2. TROSCOM MRRS units provide funds for repair parts and materiel for utility rail equipment assigned to the U.S. Army Reserve Rail Shop Units.
- 3. TROSCOM shall be reimbursed by customers other than Class I on Standard Form 1080 (Voucher for Transfer between Appropriations and/or Funds) for:
  - a. Industrial Funded Installations.



- b. DoD agencies covered by ISSA (DD Form 1144).
- c. ,Other federal agencies requesting MRRS support.
- 4. Cost and production data shall be reported in compliance with DoD 7220.29-H. (Department of Defense Depot Maintenance and maintenance support cost accounting and production reporting handbook).

#### F. SOURCE OF MAINTENANCE SUPPORT FOR LOCOMOTIVE EQUIPMENT

Mobile Rail Repair Shop (MRRS) Locations

Area Serviced

USATSARCOM MRRS #1
New Cumberland Army Depot
New Cumberland, PA 17070

Connecticut, Delaware, \*Florida, \*Georgia, Maine, Maryland, Massachusetts, Michigan, New York, New Jersey, New Hampshire, North Carolina, Ohio, Pennsylvania, Rhode Island, South Carolina, Vermont, Virginia, West Virginia

USATSARCOM MRRS #2
Red River Army Depot
Building 1535
Texarkana, TX 75501

Alabama, Arizona, Arkansas, \*Florida, \*Georgia, Illinois, Indiana, Iowa, Kansas, Kentucky, Louisiana, Minnesota, Missouri, Mississippi, Nebraska, North Dakota, Tennessee, Texas, Wisconsin

USATSARCOM MRRS #3
Tooele Army Depot
Building 502, North End
Tooele, UT 84704

Alaska, California, Colorado, Idaho, Montana, Nevada, Oregon, Utah, Washington, Wyoming

Note:

Indicates States serviced by two MRRS

MRRS #1 supports Fort Stewart, GA; and Homestead Air Force Base, FL; and Cape Canaveral, FL.

MRRRS #2 supports Government Aircraft Plan #6, Marietta, GA; Marine Corps Supply Depot, Albany, GA; Moody Air Force Base, Valdosta, GA; and Warner Robins Air Force Base, GA.



#### REPAIR AND REPLACEMENT STANDARDS FOR LOCOMOTIVES

#### A. GENERAL

1. Replacement or remanufacture of DoD locomotives shall be authorized in accordance with the provisions of this chapter. The procedures outlined shall be used to determine the expenditure limits for locomotive repairs or eligibility for replacement.

#### B. ONE-TIME REPAIR EXPENDITURE LIMITS

#### 1. Procedure.

- a. One-time repair expenditure limits are applicable each time an item becomes unserviceable. The one-time repair expenditure limit is expressed as a percentage of the total repair cost estimate to the total cost of the end. item.
- b. The procedure for determining the repair expenditure limit for an item follows:
  - (1) Establish current replacement cost.
- (2) The repair cost estimate is the sum total of the estimated cost of labor and parts listed in the technical inspection repair as necessary requirements for the restoration of an end item to a serviceable condition.
- c. Repair eligibility shall be determined by comparing the repair cost estimate with the product of the percentage, shown on the applicable repair limitations chart, times the current replacement cost of the unserviceable end item. An end item loses its repair eligibility if the estimated cost of repair exceeds this product. The maximum allowable one-time overhaul allowance of 65 percent is restricted to those years identified in Appendix A.

#### 2. Expenditure Limits.

- a. The repair expenditure limit for components, assemblies, and renewable parts applicable to end items which are serviceable or are eligible for repair is 65 percent of the estimated replacement cost. New components, assemblies, and recoverable spare parts should be procured if the estimated repair cost exceeds 65 percent of the replacement cost.
- b. Paragraph a above is applicable to bulk components, assemblies, and/or recoverable repair parts to be repaired and returned to the pipeline for issue. These bulk items are those items in support of the direct exchange program.
- c. <u>General</u>. Appendix A furnishes one time repair and/or overhaul expenditure limits in percentages of price according to age of the equipment in years and provides the necessary data required to determine end item repair eligibility. All items are identified by National Stock Numbers and arranged in numerical sequence.

Column Data: '

/a. Column (1) lists the NSN (National Stock Number) for the end item.

- b. Column (2) lists the equipment and end item nomenclature.
- c.  $\square$  column (3) lists the production year of equipment for the road and serial number listed in column (4). An asterisk in this column indicates the production year is not available.
  - d. Column (4) lists the road or serial number when available.
- e. Column (5) lists the equipment age and percentage of repair expenditures allowed, in relationship to age. Lines (1) and (3) list the age of the equipment. Lines (2) and (4) list the percentages to be used to determine the repair expenditures. Lines (1) and (3) indicate the **life** expectancy of the item in years.

#### NOTE:

Rail items to be shipped overseas or to units for movement overseas shall have a minimum of five years repair eligibility remaining  $\operatorname{sub}$ -sequent to issue. Items to be shipped to CONUS users shall have a minimum of one year repair eligibility remaining subsequent to issue.

#### c. TECHNICAL INSPECTIONS

Each locomotive shall be inspected by an experienced, technically qualified rail technican at least once annually. Unserviceable equipment shall be inspected by a qualified rail technician prior to repair or evacuation of the item to the next higher supporting maintenance facility for repair or disposal action. The inspection report shall include defects and malfunctioning components and the repair cost estimate to place the equipment in standard operating condition. The objectives of the technical inspection are:

- 1. To determine the economical reparability of DoD material.
- 2. To prevent the evacuation of uneconomically reparable equipment unless specifically required and directed.
- 3. To preclude the loss of materiel to the DoD solely on the basis of the age of the materiel.

#### D. COMPUTATION OF REPAIR COST ESTIMATES

Before preparing detailed cost estimates review previous work orders to determine whether similar items in a similar repairable condition have been repaired. If a work order exists, use actual work order cost as the estimating basis. Old work order cost should be accelerated by using prescribed operation and maintenance inflation factors to reach an estimate of repairing the component.



- 1. <u>Cost elements</u>: when past experience for repairing similar components is not available to determine estimated repair costs, detailed cost computations will be necessary.
- a. Elements of cost to be used in estimating the cost of repair or overhaul of materiel are:
  - (1) Direct labor (military and civilian).
  - (2) Direct materiels.
  - (3) Indirect or overhead costs.
  - (4) Contractual services.
  - (5) Shipping and transportation costs.
  - (6) Other charges.
- b. The following elements of cost shall not be included in depot repair or overhaul unit cost estimates:
  - (1) Replacement of nonintegral components of basic issue items.
- (2) Items of operating expense; for example, replacement of batteries, antifreeze, and petroleum products, except where the replacement is required as a result of accidental damage.
- (3) The labor cost of applying Modification Work Order's except if the amount of modification labor is small so that no major material distortion in either modification or other depot maintenance costs will occur.
- (4) The cost to overhaul or replace accessory items used to adapt materiel for special uses.

#### 2. Estimated direct labor costs.

- a. Direct labor is that labor, civilian or military, which can be specifically identified to the repair or overhaul job to be performed. It includes only those personnel that have direct productive contact with the materiel or service involved. Initial and final inspections are included in this category.
- b. To estimate direct labor costs, determine the direct labor man-hours to be applied; then, apply current pay rates plus the cost of **annual**, sick and other leave and government contributions for employee benefits.
- c. The determination of the direct labor man-hours to be applied shall be based on man-hour requirements for maintenance tasks listed in applicable materiel publications, commercial flat rate manuals when appropriate, similar work previously performed, or individual experience.
- 3. <u>Civilian labor rates</u>. Costs of civilian labor shall be based on the labor rate of the individuals who actually perform the maintenance service, as follows:



- a. Convert man-years to average productive working hours when civilian labor pay scales are stated in terms of annual salaries.
- b. Labor rates, whether determined from annual salaries or hourly wage rates, shall be computed to include provisions for the cost of annual, sick, and other leave, and government-contributed fringe benefits.
- 4. Military labor rates. Labor rates used for military personnel shall be the average military wage rate for the individuals performing the work based on standard rates.
- 5. <u>Labor rates including indirect expenses</u>. Heads of DoD components or their designees may establish and use standard hourly rates for direct labor (including indirect or overhead). When these standard rates are established, separate rates will be established **for** direct support, general support, and depot for the following:
  - a. Each category of supportable materiel listed below:
    - (1) Rail.
  - b. Each major geographical area where wage levels vary greatly.

#### 6. Estimate direct materiels costs.

- a. Estimates of costs of all materiels directly applied and identifiable to the particular item to undergo repair or overhaul shall be included in repair and overhaul cost estimates. This includes cost of government-furnished materiel used by a contractor in performing all or part of the maintenance jobs.
- b. Estimates of consumables shall be at the standard inventory price as published in appropriate supply manuals. Materiel to be obtained from local sources shall be priced at the latest invoice cost. Cost of materiel made or to be made will be the" actual cost of fabrication. When actual costs are not available, engineering estimates will be used.
- c. Replacement parts and assemblies used in the repair process shall be at the exchange price. This is the standard inventory price less credit for the return of unserviceable reparable parts removed from the particular materiel. The applicable commodity manager may prescribe a standard credit as a percent of the standard inventory price, as long as it reflects the estimated cost to repair the returned or removed repairable part.

#### 7. Estimated indirect and overhead costs.

- a. The repair or overhaul cost estimate shall include the indirect or overhead costs associated with the repair and overhaul process. These costs shall be determined by applying the indirect or overhead rate to the estimated direct labor  $\square$  an-hours.
- b. The indirect or overhead costs used in developing the indirect or overhead rate will include:

- (1) Manufacturing or production expense, such as indirect costs incurred within or identifiable to the maintenance shop or organization performing the **repair** work, although not identifiable to a particular repair or overhaul job.
- (2) General and administrative expenses, such as costs incurred in general management or supervision, which are measurable costs chargeable to maintenance units and activities.
- 8. <u>Contractual services</u>. These are costs for contractual. services required, incident to, or identifiable with the performance of all or part of the specific maintenance job and will be included in the cost estimate.
- 9. <u>Shipping costs</u>. All shipping costs shall be included in the estimate. Shipping costs include:
- a. All costs involved in preparing the materiel for shipment at point of use; and
- b. All transportation and handling costs from point of use to selected point of repair.
- 10. Estimates of other costs. Any other costs, not excluded in paragraph lb., Section D required to complete the required maintenance which can be directly identified to the repair or overhaul task, shall also be included in the estimate, although not specifically mentioned herein.

#### 11. Commodity manager adjustment of cost and man-hour estimates.

- a. When materiel is reported to commodity manager for disposition instructions based on repair cost estimates, the commodity manager shall compare the labor rate used by field personnel with the labor rate of the depot maintenance facility selected to complete the maintenance required. Adjustments in the repair cost estimate to reflect depot maintenance labor rates shall be made prior to a decision concerning the disposition of the unserviceable asset.
- b. When materiel is reported to the commodity manager for disposal/instructions commodity manager based on man-hour estimates, shall convert the direct labor man-hours and related information identifiable to the maintenance effort required to a repair **or** overhaul cost estimate in dollar amounts per this regulation. This shall be done prior to a decision concerning the disposition of the materiel.

#### 12. Waivers by major commands

ming and !

Free Contraction of

- a. Heads of DoD components or their designees have approval authority on requests for waivers of published maximum repair and overhaul allowances when the required maintenance can be accomplished at organizational, direct support, or general support categories of maintenance. Required repairs shall not be broken into separate job estimates merely to by-pass prescribed maximum repair allowances.
  - b. In approving such requests, commanders will insure that:

- (1) The unit or organization requesting the waiver has been unable to obtain timely replacement of the uneconomically reparable asset by checking with the appropriate commodity manager.
- (2) An urgent operational or essential training requirement exists, which justifies the uneconomical repair.
- (3) Resources are available (or can be made available) to the requesting organization or command to do the required repairs within an acceptable period of time. Normal maximum time is considered 60 days.
- (4) Unit and activity commanders requesting materiel waivers shall submit copies of the technical inspection report with justification for materiel retention and uneconomical repair, through proper support maintenance channels, to DoD service commanders for approval.
- 13. <u>Waivers by NMP/NICP</u> NICPs, in coordination with the proper NMP, may grant waivers to published maximum one-time repair and overhaul allowances when the maintenance required to restore the unserviceable asset to a serviceable condition will be accomplished at the depot maintenance level, and operational requirements necessitate such action.

#### E. DISPOSITION INSTRUCTIONS

- 1. Eligibility of Materiel for Evacuation to Depot Maintenance.
- a. <u>CONUS</u>. All locomotives covered by this chapter are eligible for evacuation to depot maintenance whenever the Technical Inspection results indicates that repairs required are not authorized and/or exceed general support capabilities. The cost of repairs shall not exceed the one-time repair expenditure limits.
- b. Overseas. Depot maintenance of all locomotive end items at overseas installations is the responsiblity of major 'overseas commanders. It shall be accomplished with existing facilities, personnel, and equiPment with appropriate augmentation when required, or by contract maintenance. The technical inspectors must be familiar with Daintenance operations and standards to determine the work required and thereby arrive at the ProPer classification.
- 2. <u>Disposition Instructions</u>. These instructions shall be provided by the commodity manager for all **locomotives** regardless of repair expenditure limitations listed in the applicable appendix. When the estimated one-time repair cost exceeds the prescribed expenditure limits and waiver of limits is not authorized, no action will be taken to dispose of the equipment until disposition instructions are received from the NICP.

#### STORAGE OF LOCOMOTIVES

#### A. POLICY

1

Locomotives authorized under the provisions of Chapter 3 may be placed in storage when there is no immediate requirement for the equipment, but it must be retained for contingency or other valid reasons. Consideration will be given to retaining the locomotive in active service through a rotation program with assigned locomotives in operation at the installation to which the unit is assigns. The high acquisition cost, the long procurement cycle the transportation costs incurred in the movement or reassignment, and the time frame required to secure a locomotive or replacement are factors to be considered in determining if a locomotive should be retained in storage or declared excess. Locomotives placed in storage shall be processed in accordance with the applicable regulations of the DoD Component owning the locomotive. The Department of the Army Technical Bulletin TB 740-93-5, "''Preservation of Railroad Equipment for Storage," may be used instead of service regulations.

#### B. STORAGE LOCATIONS

The following factors shall be weighed in determining storage locations for locomotives:

- 1. Strategic location in relation to mobilization or emergency requirements.
- 2. Availability of rail trackage.
- 3. Resource availability **for** dynamic dehumidification (cocooning) and enclosed storage facilities.
  - 4. Climatic conditions.
  - 5. Access to major trunk lines.

#### c. STORAGE AT USER INSTALLATIONS

Administrative storage, wherein the user installation places the locomotive in a limited care and preservation status in accordance with applicable technical manuals for short periods of time, is authorized. The allowable time that a locomotive may remain in adminstrative storage will vary with the storage environment. Locomotives placed in this type storage will be capable of being restored to full mission capability within 30 days. Prior to placing the locomotive in storage, the next scheduled preventive maintenance shall be performed and deficiencies shall be corrected. All regularly scheduled preventive maintenance services shall be suspended when the unit is placed in storage. Locomotives removed from storage will be restored to normal operating condition according to applicable technical manuals and tested to determine their operational capability.

#### D. LONG TERM STORAGE

Long term (in excess of five years) storage shall be restricted to locomotives that cannot be leased or acquired in time to meet contingency requirements. Dynamic dehumidification (cocooning) should be considered when it is anticipated that the locomotives may be retained in storage in excess of five years. When economically and operationally feasible, locomotives should be stored in areas with climatic conditions conducive to preservation without dehumidification. Such storage will facilitate the rotation in usage of the locomotives in long term storage and make it possible to expeditiously place locomotives in service in emergencies.

#### CHAPTER 11

#### SAFETY

#### A. OPERATING AND SAFETY RULES

Operating and Safety Rules for railroad operations will be published and kept current by the DoD Components. The Standard issued by the Association of American Railroads may be modified to apply to the conditions prevailing in the operations of the individual components. The joint Army/Air Force technical manua 1, TM 55-200 "Railway Operating and Safety Rules", may be used by the other DoD components instead of preparing and maintaining individual publications. Safety rules applicable to railroad operations are incorporated into TM 55-200.

#### B. SAFETY REQUIREMENTS--LOCOMOTIVES

The following general requirements are applicable to the operation and maintenance of all DoD locomotives.

1. Protection against personal injury. Fan openings, exposed gears and pinions, exposed moving parts of mechanisms, pipes carrying hot gases and high-voltage equipment, switches, circuit breakers, contractors, relays, grid resistors, and fuses shall be in non-hazardous locations or equipped with guards to prevent personal injury.

#### 2. Exhaust and battery gases.

- a. Products of combustion shall be released entirely outside the cab and other compartments. Exhaust stacks shall be of sufficient height, or other means provided to prevent entry of products of combustion into the cab or other compartment under usual operating conditions.
- b. Battery containers shall be vented, and batteries kept from gassing excessively.
- 3. General condition. All systems and components on a locomotive shall be free of conditions that endanger the safety of the crew, working on or about locomotives or train. These conditions would include: insecure attachment of components including third rail shoes or beams, traction motors, motor gear cases, and fuel tanks; fuels, oil, water, steam, and other leaks and accumulations of oil on electrical equipment that would create unnecessary risk; improper functioning of components, including slack adjusters, pantograph operating cylinders, circuit breakers, contractors, relays, switches, and fuses; and cracks, breaks, excessive wear and other structural infirmities of components including quill drives, axles, gears, pinions, pantograph shoes and horns, third rail beams, traction motor gear cases, and fuel tanks.
- 4. Leaving locomotive unattended. Normal circumstances should not require an engine running locomotive to be left unattended. For unusual cases when it is necessary to leave an engine running locomotive unattended, the following procedure should be followed.



- a. Securely apply locomotive hand brake.
- b. Place engine run and generator field switches in the OFF (down)  $\ensuremath{\mathbf{position/}}$
- c. Place throttle in IDLE and dynamic brake in OFF position. Remove reverser handle from controller to lock the controls.
  - d. Observe all Railroad Safety precautions.

## APPENDIX A MAINTENANCE REPAIR EXPENDITURE LIMITATIONS FOR FSCC 2210 (LOCOMOTIVES)

NSN	Item Identification	Prod. Yr.	USA Road NR Range						Repair Expenditure Limits in Percentage of Price According to Age in Years  2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18													
2210-00-112-8508	Locomotive, Diesel,	1942	7103, 7122, 7274,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Electric, 115 Ton, <b>DS</b> , ALCO Model 539S	1943	7101, 7108	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38
	ALOO Wodel 5555			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						
2210-00-142-0230	Car Spotter, DS, 8400	1952	T-7. T-12	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Lb. Draw <b>Bar Pull,</b> Whiting Corp.	1953 1955	T-6; T-10 T-2, T-3, <b>T-8</b> , T-9, T-I4,	%	49	49	48	46	45	44	43	41	40	38	36	34	32	30	27	24	20	12
	William g Colp.	1000	T-15, T-17	Υr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%																		
2210-00-262-0751	Locomotive, Diesel,	1953	1843, 1844, 1846 thru 1853,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Electric, 120 Ton, DS, Fairbanks-Morse Hı 2-44		1855 thru 1862	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38
Talibaliks-Worse Til 2-44		Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36		
				%	36	35	33	32	30	28	26	24	21	18	15	10						[ .
2210-00-371-7535	locomotive, Diesel,	1951	2000, 2002, 2007 thru 2010,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Electric, 100 Ton, DS, Electro-Motive SW-8		2012 thru 2016, 2018 thru 2022, 2024, 2027 thru 2030,	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38
	LICONO MICRIO CITO		2034 thru 2038	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						
2210-00-529-9038	Locomotive, Diesel,	1944	7926, 8566, 8574, 8580, 8583	Yr	1	2	3	4	5	6	7	8	9	1100	1111	12	13	14	15	16	17	16
	Electric, 45 Ton, D&FS, GE/Caterpillar Eng.			%	50	49	49	48	48	48	47	47	46	46	45	44	43	42	41	40	39	38
	OL/Outo/pillar sing,			YΓ	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						i
2210-00-543-3289	Car Spotter, DS, 13000	1956	T-423	Yr	1	2	3	4	5	6	7	_8	9	10	11	12	13	14	115	116	1177	1188
	Lb. Draw Bar Pull, Whiling Corp.	1957	T-II, T-13	%	49	49	48	46	45	44	43	41	40	38	3 <b>6</b>	34	32	30	2277	2244	2 <b>20</b> 0	12
	9 55.6.			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%																		

NSN	ltem Identification	Prod. Yr.	USA Road NR Range	Repair Expenditure Limits in Percentage of Price According to Age in Years																					
2210-00-554-0784	Locomotive, Diesel,	1943	7750	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			
	Electric, 25 Ton, 36"			%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	Gage, FS, GE/Cummins HBI 600			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
	, 10. 000			%	36	35	33	32	30	28	26	24	21	18	15										
2210-00-554-0785	Locomotive, Diesel,	1951	1822, 1823, 1824, 1829, 1 <b>1832,</b>	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			
	Electric, 120 Ton, DS,		1635	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	EMD GP7L			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
				%	36	35	33	32	30	28	26	24	21	18	15	10									
2210-00-804-3610	Locomotive, Diesel,	1953	1216, 1217, 1221 thru 1235,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			
	Electric, 44 Ton, <b>DS</b> ,		and 1227 thru 1231	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	Davenport-Besler			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
				%	36	35	33	32	30	28	26	24	21	18	15	10									
2210-00-804-3611	Locomotive, Diesel, Electric, 120 Ton,	Locomotive, Diesel,	Locomotive, Diesel,	Locomotive, Diesel,	1952	1841, 1842, 1863, 1864	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
				%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	<b>D&amp;</b> FS, Baldwin 606A			Yr	19	20	21	22	23	24	25	26	26 27 28 2	29	30	31	32	33	34	35	36				
				%	36	35	33	32	30	28	26	24	21	18	15	10									
2210-00-804-3614	Locomotive, Diesel,	1952	1636, 1637, 1639 thru 1642,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	่ 16	17	18			
	Electric、80 Ton, <b>DS.</b> <b>GE/NHBIS</b> 6 0 0 "		1644 thru 164. <b>7,</b> 1649, 1650, 1651, 1653 thru 1659, 1661	0/_0	<del>ნ</del> ეŪ	19 J	ر به إ	199	ر 48	48	47	47	46	46	45	44	43	42	41	40	<b>39</b> 38				
	GE/NOIS 600		thru 1665, <b>1667 thru 1685</b>	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
		Ϊ		%	36	35	33	32	30	28	26	24	21	18	15	10									
221040-804-3615	Locomotive, Diesel, Electric, <b>80</b> Ton, 0S, Davenport <b>Besler</b>	1952	1622 thru 1625, 1627, <b>162</b> 8,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			
			1632 thru 1634	%	50	49	48	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
				Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
				%	36	35	33	32	30	28	26	24	21	18	15	10									
2210-00-814-5291	Locomotive, Diesel,	1953	2091, 2095, 2096, 2104, 2108	Yı	1	2	3	4-	5	6	7	8	9.	10	11	12	13	14	15	16	17	18			
	Electric, 120 Ton, DS,			%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	D&FS, GE/ALCO			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
				%	36	35	33	32	30	28	26	24	21	18	15	10									
2210-00-815-3521	Locomotive, Diesel,	1953	B2041 thru B2044, B2046 thru	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18			
	Electric, 120 Ton,		B2090	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38			
	D&FS GE/ALCO W/Steam Generator			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36			
	22.00.000			%	1	35	1		ļ		<del>                                     </del>		21	18	15	10									

NSN	Item Identification	Prod. <b>Yr.</b>	USA Road NR Range	Repair Expenditure Limits in Percentage of Price According to Age in Years																							
2210-00-819.9317	Locomotive, Diesel,	Locomotive, Diesel,	Locomotive, Diesel,	Locomotive, Diesel,	Locomotive, Diesel,	Locomotive, Diesel,	1952	1808, 1809, 1810, 1812, 1813,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Electric, 120 Ton, D&FS, EMD-MRS-1		1820	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38					
	Day of EMD MINO-1			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	.%	36					
				%	36	35	33	32	30	28	26	24	21	18	15	10											
2210-00-819-9318	Locomotive, Diesel,	1954	1247 thru 1273, 1275, 1276,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
	Electric, 60 Ton,. <b>D&amp;FS</b> , Baldwin-		4001 thru 4044	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38					
	Lima-Hamilton			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
				%	36	35	33	32	30	28	26	24	21	18	15	10											
2210-00-819-9320	Locomotive, Diesel,	1941	7277,7370,7371,7374, 7459,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
	Electric, 100 Ton, DS, ALCO Model 539.	1942	7460 1807, 7132, 7133, 7134	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38					
		1012		Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
				%	36	35	33	32	30	28	26	24	21	18	15	10											
2210-00-820-5451	Locomotive, Diesel,	1941	7363, 7448	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
	Electric, 80 Ton, DS, GE/Cummins LL600	1942	7145, 7201, 7267, 7373, 7376, 7389	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38					
	GE/Command Ecoop	1943	7144, 7851, 7855, 7856, 7858,	Yr	19	20	21	22	23	<del>╌┍╏╍┈┝┈┈┠┈┈┟╸┈╽┈┈┞┈┈┝┈┈┟┈┈╸</del> ┟	32	33	34	35	36												
			7860, 7863, 7890, 7891, 7896	%	36	34	33	32	30	28	26	24	21	18	15	10											
		1945	7393, 7394 1605, 1606, 1607, 1686, 1687, 1688, 1691, 1692, 1693, 1694	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
	19	1953		%																							
		1954	1689, 1690	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
				%																							
2210-00-820-56011,	Locomotive, <b>Diesel</b> , Electric, 120 Ton, <b>DS</b> , Baldwin S/VO 8	1943	7126, 7467	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
				%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38					
•		İ		Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
				%	36	35	33	32	30	28	26	24	21	18	15	10											
22100000820-5602	Locomotive, Diesel,	1942	<b>7064.</b> 7095	Yr	1.	2	3	4	5	6	7	a	9	10	11.	<u>17</u>	13	14	15	16	17	18					
	Electric, 44 Ton, DS, GE/Caterpillar D-1 7000	1943	7439, 7492, 7493, 7494, 7516,	%	50	49	49	49	48	48	47	47	46	46	45	.44	43	42	41	40	39	38					
	GE/Caterpillal D-1 7000		7931	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
				%	36	35	33	32	30	26	26	24	21	18	15	10											
2210-00-821-1135	Locomotive, Diesel,	1941	7041,7078,7071,7091, 7209,	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18					
	Electric, 45 Ton, 0S, GE/Cummins HBI 600	7242,7243,7245,7320, 7323,					49	49	48	48	47	47	46	46	45	44	43	42	ነ 4"ነ '	40	39	38					
	JE/Cummins HDI 000		7324,7330,7331,7332, 7355, 7356, 7937	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36					
		1942	1207, 7048, 7071, 7077, 7089	%	36	35	33	32	30	28	26	24	21	18	15	10											

NSN	<b>Item</b> Identification	Prod. Yr.	USA Road NR Range	Repair Expenditure Limits in Percentage of Price According to Age in Years																		
		7249,7251,7404,7406, 7408, Y		, 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
		4040	7472,7413,7417,7440, 7441, 7486, 7797, 7936 7318,7254,7496,7497, 7498, 7955, 7957 8537  "/0  1032 thru 1061  Yr							0.1	0.5								-		<u> </u>	
		1943		Уг	19	20	21	22	23	24	25	26	27	28	29	30	3,	32	33	34	35	36
		1944																		<u> </u>		
2210-00-825-5050	Locomotive, Diesel,	1953	1032 thru 1061	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Mechanical, 10 Ton, DS, Plymouth Locomotive			%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38
Works				Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						
2210-00-834-3202	Locomotive, Diesel,	1943	1136, 1182, 7098, 7763	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	38
	Electric, 25 Ton, DS, GE/Cummins HB 1	1944 1945	0003, 7773, 7779 0001	%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	
	ac/ountilis/10/1	1952	1146	Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	
	_			%	36	35	33	32	30	28	26	24	21	18	15	10						
2210-00-837-7793	Locomotive, Diesel,	1952	1600 thru 1604, 1620, 1692	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	36 18 38 36 18 38
	Electric, 80 Ton, DS, GE/Cummins NHBIS			%	50	49	49	49	48	48	47	47	46	46	45	44	43	42	41	40	39	38
	GE/ GUITHIMIS TO ISTO			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						
2210-00-939-6648	Locomotive, Diesel,	1953	1236 thru 1246	Yr	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
	Electric, 44 Ton, DS, GE/SNGLE Station,			%	50	49	49	49	48	48	47	47	46.	46	45	44	43	42	41	40	39	38
	Multiple Unit			Yr	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
				%	36	35	33	32	30	28	26	24	21	18	15	10						

#### TAB B

- 1. DoD **Diréctive** 5000.11, "Data Elements and Data Codes Standardization Program." December 7, 1964.
- 2. DoD 5000.12-M, "DoD Manual for Standard Data Elements," December 1982.
- 3. DoD Directive 5000.19, "Policies for the Management and Control of Information Requirements," March 12, 1976.